

PCT

WORLD INTELLE

INTERNATIONAL APPLICATION PUBLISH



EP0440169

(51) International Patent Classification ⁶ :

E21B 37/06, C10L 3/00

WO 9604462A1

(43) International Publication Date: 15 February 1996 (15.02.96)

(21) International Application Number: PCT/GB95/01801

(22) International Filing Date: 28 July 1995 (28.07.95)

(30) Priority Data:

9415903.5

5 August 1994 (05.08.94)

GB

9425399.4

14 December 1994 (14.12.94)

GB

(71) Applicant: BP EXPLORATION OPERATING COMPANY LIMITED [GB/GB]; Britannic House, 1 Finsbury Circus, London EC2M 7BA (GB).

(72) Inventors: DUNCUM, Simon, Neil; 6 Cressida Chase, Warfield, Bracknell, Berkshire RG12 6UD (GB). EDWARDS, Antony, Roland; 105 Mortlake Road, Kew, Surrey TW9 4AA (GB). OSBORNE, Christopher, George; 66 Mickle Hill, Little Sandhurst, Camberley, Surrey GU17 8QU (GB).

(74) Agent: WILSON, Michael, John; BP International Limited, Group Patents & Agreements, Chertsey Road, Sunbury-on-Thames, Middlesex TW16 7LN (GB).

(81) Designated States: AU, CA, NO, NZ, VN, European patent (AT, BE, CH, DE, DK, ES, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).

Published

With international search report.

(54) Title: HYDRATE INHIBITION

(57) Abstract

A method of inhibiting or retarding formation of hydrates from water and a lower alkane, such as methane or ethane, involves adding additives which comprise (i) a corrosion inhibitor and (ii) a salt which is of formula $[R^1(R^2)XR^3]^+Y^-$, wherein each of R^1 , R^2 and R^3 is bonded directly to X, each of R^1 and R^2 , which may be the same or different is an alkyl group of at least 4 carbons, X is S, NR^4 or PR^4 , wherein each of R^3 and R^4 which may be the same or different represents hydrogen or an organic group, with the proviso that at least one of R^3 and R^4 is an organic group of at least 4 carbons, and Y is an anion, the additives being added in an amount effective to inhibit or retard hydrate formation, to a medium susceptible to hydrate formation.

Best Available Copy

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AT	Austria	GB	United Kingdom	MR	Mauritania
AU	Australia	GE	Georgia	MW	Malawi
BB	Barbados	GN	Guinea	NE	Niger
BE	Belgium	GR	Greece	NL	Netherlands
BF	Burkina Faso	HU	Hungary	NO	Norway
BG	Bulgaria	IE	Ireland	NZ	New Zealand
BJ	Benin	IT	Italy	PL	Poland
BR	Brazil	JP	Japan	PT	Portugal
BY	Belarus	KE	Kenya	RO	Romania
CA	Canada	KG	Kyrgyzstan	RU	Russian Federation
CF	Central African Republic	KP	Democratic People's Republic of Korea	SD	Sudan
CG	Congo	KR	Republic of Korea	SE	Sweden
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LU	Luxembourg	TD	Chad
CS	Czechoslovakia	LV	Latvia	TG	Togo
CZ	Czech Republic	MC	Monaco	TJ	Tajikistan
DE	Germany	MD	Republic of Moldova	TT	Trinidad and Tobago
DK	Denmark	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	US	United States of America
FI	Finland	MN	Mongolia	UZ	Uzbekistan
FR	France			VN	Viet Nam
GA	Gabon				

HYDRATE INHIBITION

The present invention relates to hydrate inhibitors and a method for inhibiting the formation of hydrates in particular to a method for inhibiting the formation of hydrates in the petroleum and natural gas industries.

Hydrates are formed of two components, water and certain gas molecules, e.g. alkanes of 1-4 carbons, especially methane and ethane, such as those found in natural gas. These 'gas' hydrates will form under certain conditions, i.e. when the water is in the presence of the gas and when the conditions of high pressure and low temperature reach respective threshold values. The gas may be in the free state or dissolved in a liquid state, for example, as a liquid hydrocarbon.

The formation of such hydrates can cause problems in the petroleum oil and natural gas industries.

Hydrate formation in the field may cause blocked pipelines, valves and other process equipment.

The problem is particularly of concern as natural gas and gas condensate resources are discovered where operating conditions surpass these threshold values, i.e. in deep cold water and on-shore in colder climates.

Hydrates can also form in association with the underground hydrocarbon reservoir thus impeding production by blockage of reservoir pores.

The problem of hydrate formation is however commonest during gas transportation and processing, the solid hydrate precipitating from moist gas mixtures. This is particularly true with natural gas which when extracted from the well is normally saturated with water. Often in such a case, in a cold climate, hydrates will form in downstream transportation networks and this can cause large pressure drops throughout the system and reduce or stop the flow of natural gas.

Hydrate formation may also occur during natural gas cryogenic liquefaction

and separation.

A typical situation where hydrate formation can occur is in offshore operations where produced fluids are transported in a long vertical pipeline, for example, a riser system. Such produced fluids normally include light gases known to form hydrates and water. In such a situation a temperature of 4.5°C and a pressure of 150 psi would be sufficient for hydrate formation.

Several methods are known to prevent hydrate formation and subsequent problems in pipelines, valves and other processing equipment.

Physical methods have been used, e.g. increasing gas temperature in the pipeline, drying the gas before introduction into the pipeline, or lowering the gas pressure in the system. However, these techniques are either expensive or are undesirable because of loss of efficiency and production.

Chemical procedures have also been used. Electrolytes, for example, ammonia, aqueous sodium chloride, brines and aqueous sugar solutions may be added to the system.

Alternatively, the addition of methanol or other polar organic substances, for example, ethylene glycol or other glycols may be used. Methanol injection has been widely used to inhibit hydrate formation. However, it is only effective if a sufficiently high concentration is present since at low concentrations there is the problem of facilitation of hydrate formation. Also for methanol to be used economically under cold environmental conditions there must be early separation and expulsion of free water from the well in order to minimise methanol losses in the water phase.

We have now found certain additives which may be used as effective hydrate inhibitors at low concentrations. Thus according to the present invention, there is provided a method of inhibiting or retarding hydrate formation, which method comprises adding additives (hereinafter called Additives) which comprise (i) a corrosion inhibitor and (ii) a salt which is of formula $[R^1(R^2)XR^3]^+Y^-$, I wherein each of R^1 , R^2 and R^3 is bonded directly to X, each of R^1 and R^2 , which may be the same or different is an alkyl group of at least 4 carbons, X is S, NR^4 or PR^4 , wherein each of R^3 and R^4 which may be the same or different represents hydrogen or an organic group, with the proviso that at least one of R^3 and R^4 is an organic group of at least 4 carbons, especially at least 5 carbons, and Y is an anion, the additives being added in an amount effective to inhibit or retard hydrate formation, to a medium susceptible to hydrate formation.

The Additive (i) is a corrosion inhibitor eg. for steel and usually one suitable for

use in anaerobic environments. It may be a film former, capable of being deposited as a film on a metal eg. a steel surface such as a pipeline wall. It preferably has surfactant activity and especially surface wetting activity.

It is especially a nitrogenous compound with 1 or 2 nitrogen atoms. The corrosion inhibitor may be a primary, secondary or tertiary amine, or a quaternary ammonium salt, usually in all cases with at least one hydrophobic group, usually a benzene ring or a long chain alkyl group eg. of 8-24 carbons. It may be a quaternary ammonium salt, a long chain aliphatic hydrocarbyl N-heterocyclic compound or a long chain amine. The quaternary salt may be an (optionally alkyl substituted) benzyl trialkyl ammonium halide, in particular when at least 1 and especially 1 or 2 alkyl groups is of 1-20, in particular 8-20 carbons such as cetyl and the other alkyl groups are of 1-6 carbons such as methyl or ethyl; examples are benzyl alkyldimethyl ammonium chloride and Benzalkonium chlorides.

Other quaternary ammonium salts may be of formula $[R^5R^6NR^7R^8]^+Z^-$, wherein Z is an anion eg. a halide or sulphate, R^5 is an alkyl or alkenyl group of at least 8 carbons, R^6 is an alkyl or alkenyl group, each of at least 2 carbons or a N-heterocyclic group, and R^7 and R^8 , which may be the same or different represents an alkyl group, with the proviso that at least one of $R^6 - R^8$ has less than 4 carbon atoms. R^5 may be of 8-24 carbons, such as 10-18 carbons, especially, dodecyl, lauryl, cetyl, palmityl, stearyl or oleyl, while R^6 may be selected from the same groups as R^5 , or may be ethyl, propyl, isopropyl, butyl or hexyl. R^7 and R^8 may be selected from the same groups as R^6 but preferably represent methyl groups. Examples of these quaternary salts are cetyl trimethyl ammonium, dodecyl trimethylammonium and lauryl trimethylammonium halides, eg. chlorides or bromides.

Other quaternary salt corrosion inhibitors are of formula $[R^9NR^{10}R^{11}]^+Z^-$ where Z is a anion eg. as defined above, R^9N or R^9NR^{10} forms a quaternizable N heterocyclic ring, and R^{11} represents an alkyl or alkenyl group each of at least 8 carbons eg. as described for R^5 . The R^9N group may be N- heterocyclic group with 1 or 2 ring N atoms, especially with 1 or 2 heterocyclic rings, eg. of 5 or particularly 6 ring atoms; examples of the rings are saturated ones eg. piperidine. The group R^9NR^{10} may also be such an N heterocyclic group but with the R^9 and R^{10} groups combined with the N atom to which they are bonded to form an unsaturated ring or fused N bridged ring system such as a pyridine ring. R^{10} if present may otherwise be an alkyl or alkenyl group eg. as described for R^8 . Examples of these quaternaries are cetyl pyridinium halides, such as the chloride.

The corrosion inhibitor may also be a long chain aliphatic hydrocarbyl N-heterocyclic compound, which is not quaternised. The aliphatic hydrocarbyl group in the heterocyclic compound usually has 8-24 carbons in the hydrocarbyl group, preferably a linear saturated or mono or diethylenically unsaturated hydrocarbyl group; cetyl-, stearyl and especially oleyl- groups are preferred. The N-heterocyclic compound usually has 1-3 ring N atoms, especially 1 or 2 which usually has 5-7 ring atoms in each of 1 or 2 rings; imidazole and imidazoline rings are preferred. The heterocyclic compound may have the aliphatic hydrocarbyl group on an N or preferably C atom in the ring; the ring may also have an amino-alkyl (e.g. 2-amino ethyl) or hydroxyalkyl (e.g. 2-hydroxyethyl) substituent, especially on an N atom. N-2-aminoethyl-2-oleyl-imidazoline is preferred. The long chain amine usually contains 8-24 carbons and preferably is an aliphatic primary amine, which is especially saturated or mono ethylenically unsaturated; an example is dodecylamine. Mixtures of any of the above corrosion inhibitors with each other may be used, eg a quaternary ammonium salt and a long chain aliphatic hydrocarbyl-N-heterocyclic compound (where each is preferably as described above), or mixtures with a tertiary aliphatic amine.

If desired the corrosion inhibitor eg. a long chain amine may also comprise a phosphate ester salt, especially one with surface wetting activity. Such phosphate esters are anionic surfactants, which are salts of alkali metals eg. sodium or a quaternary ammonium eg. tetra methyl ammonium or tetrabutyl ammonium salts of acid phosphate esters, eg. with 1 or 2 organic groups and 2 or 1 hydrogen atoms; examples of the organic groups are alkyl or alkenyl groups as described for R⁵ above. Examples of such phosphate ester salts are mono and dioctyl acid phosphate salts and mixtures thereof. A preferred blend comprises a long chain alkylamine and a phosphate ester salt eg. as sold as NAL 1272 by Nalco.

The other essential Additive (ii) is a salt of formula I, $[R^1R^2XR^3]^+Y^-$, in which each of R¹ and R² is an alkyl group of at least 4 carbons, which may be a linear alkyl or branched alkyl group, eg. a secondary or tertiary alkyl group or especially an isoalkyl group. Each of R¹ and R² may be an alkyl group of 4-24 carbons, preferably 4-10 and especially 4-6 carbons, such as n-butyl, isobutyl, secbutyl, tertiary butyl, n-pentyl, sec pentyl, isopentyl or tertiary pentyl group, or hexyl group. R³ and R⁴ (if present as is preferred) are each hydrogen or an organic group eg. of 1-24 carbons such as an alkyl or alkenyl group each preferably of 8-20 carbons, eg. as is described for R⁵ above; however at least one of R³ and R⁴ contains at least 4 carbons eg. at least 5 carbons, especially in a group with a linear chain containing such numbers of

carbon atoms. R^3 may preferably be an alkyl group of 10-16 carbons, especially a mixture of 2 or more such alkyl groups. R^4 may be hydrogen but is preferably alkyl of 1-10 carbons, eg. methyl or ethyl but especially of 4-6 carbon atoms, such as is described for R^1 or R^2 . Y is an anion which may be mono- or divalent and may be as defined for Z above. Preferred salts are tetra n-butyl, tetra n-pentyl, tetra-iso-pentyl ammonium (and phosphonium) halides eg. chlorides or especially bromides, and C_{10-16} alkyl tri n-butyl ammonium (and phosphonium) halides, especially chlorides or bromides. Tri n-butyl, n pentyl or isopentyl sulphonium halides eg. chlorides or bromides may be used.

The Additives (i) and (ii) may be present in weight ratios of 1-99:99:1 such as 10-90:90:10, but especially with a weight excess of Additive (ii) such as with a ratio of (i) to (ii) of 10-45:90-55. Mixtures of the Additives (i) and (ii) form another aspect of the invention, so there is also provided a blend which comprises a mixture of at least two Additives (i) and (ii).

The Additives (i) and (ii) for use as hydrate inhibitors are preferably water soluble, e.g. to at least 10 g/l in water at 20°C. They may be used undiluted, but preferably are in solution such as aqueous solution, for example, as a solution in brine, or preferably an alcohol, for example, a water miscible one such as methanol or ethanol. Preferably are used Additives (i) and (ii), an aqueous solution of which has a pH 1.5-12, e.g. 4-9, either naturally or after adjustment of the pH. Additives (i) and/or (ii) may be used in alcoholic solution.

Each Additive is suitably injected at concentrations in the range 10 to 20,000 ppm, e.g. 30 to 10,000 ppm, especially 50-1200 ppm based on the total water volume in the medium, in which hydrate formation is to be inhibited, in particular at concentrations in the range 100-2000 e.g. 200-1500 ppm for Additive (i) and 300-6000 e.g. 500-5000 ppm for Additive (ii). The amount of methanol, ethanol, or mono, di or tri ethylene glycol added relative to the total water volume in the medium is usually less than 10%, e.g. less than 5% or 2%, but especially less than 10,000 ppm, eg 1000 - 8000 ppm.

The inhibitors may be injected at normal ambient conditions of temperature and pressure.

There may also be present with the Additive (i) at least one Additive (ix) which is at least one water soluble polymer of a polar ethylenically unsaturated compound and/or at least one Additive (x) which is a hydrophilic colloid. The Additive (ix) is usually water soluble to at least 10 g/l at 20°C and advantageously has a molecular

weight of 1000-1500,000, e.g. 5000-1,000,000, preferably 200,000-1,000,000 and especially 400,000-900,000. The ethylenically unsaturated compound is preferably a vinyl or methyl vinyl group, and the polar group may be an alcohol, carboxylic acid, sulphonic acid or N-heterocyclic group, especially pyrrolidone. Preferred polar
5 compounds are thus vinyl sulphonic acid, acrylic and methacrylic acids and N-vinyl pyrrolidone and "vinyl alcohol". The polymers may be copolymers, but are preferably homopolymers of these polar compounds, especially polyvinyl alcohol (e.g. hydrolysed polyvinyl acetate), polyacrylates and polyvinyl pyrrolidone (PVP). The amount of said polymer is usually 10-1000%, such as 50-300% or 90-250% based on the weight of
10 the total of Additive(s) (i) and (ii).

The hydrophilic colloid is an organic solid which is soluble in boiling water, e.g. to at least 10 g/l or dispersible in boiling water and may be soluble (at least 10 g/l) or dispersible in water at 20°C. It usually absorbs water strongly, e.g. to at least three times such as 3-15 times its weight of water at 20°C, and swells in water. It can form a
15 colloidal solution or dispersion in water and may have an average molecular weight of at least 10,000, e.g. 100,000-10,000,000. It may be a polysaccharide, e.g. with at least 4 carbohydrate units, especially one with at least some galactose units, e.g. 20-60% of such units, and may contain carboxylic acid residues, so that an aqueous solution or dispersion thereof can have an acidic reaction. The polysaccharide may be a natural
20 gum, e.g. guar, agar, arabic, locust bean, karaya, carob or tragacanth gum, or a cellulosic material, such as starch, which may be unmodified or modified as an alkyl ether, e.g. methyl or ethyl cellulose or hydroxyalkyl ether, e.g. hydroxyethyl cellulose or carboxy alkylated starch, e.g. carboxy methyl cellulose (CMC). The polysaccharide may also be a synthetic, e.g. biosynthetic gum, the result of a microbiological process,
25 e.g. fermentation; xanthan gum, which can be made by fermentation of dextrose with Xanthomonas campestris cultures, which is preferred, especially water soluble versions of xanthan gum. The colloid may also be proteinaceous, in particular gelatin or carrageenan (a seaweed extract), e.g. x-carrageenan. The colloid may also be a polyuronic acid or salt thereof, e.g. sodium or ammonium salt or ester thereof, such as
30 a hydroxy alkyl ester (e.g. of propylene glycol), especially with beta-D-mannuronic acid residues; alginic acid and especially sodium alginate is preferred. The amount of Additive (x) may be 10 - 1000%, eg 50 - 300% or 90 - 250% by weight based on the total weight of Additives (i) and (ii).


Preferably there is present as Additive (xi) a Polymer of an ethylenically
35 unsaturated N- heterocyclic carbonyl compound. The Polymer has a hydrocarbon

chain with pendant N-heterocyclic carbonyl groups, with the bonding to the chain via the heteroring -N- atom. The carbonyl group may be in any position in the N heteroring, but is especially alpha to the N hetero atom, so the N-heterocyclic rings are preferably derived from lactams, especially of 4-8 eg 5 or 6 ring atoms, such as those
 5 derived from butyric, pentenoic, pentanoic or hexanoic acid lactams (or 2-pyrrolidone, 2-pyridone, 2-piperidone or omega caprolactam). The polymer may have structural units from N- vinyl pyrrolidone and may be a homopolymer or copolymer, whether a graft copolymer or otherwise.

Preferably the Polymer as Additive (xii) has an aliphatic (N-heterocyclic carbonyl) polymer with a hydrocarbon backbone. It is water soluble or water
 10 dispersible, eg to an extent of at least 0.01% by weight in water such as at least 0.05% but especially at least 0.5%, such as up to 10% by weight. Its molecular weight is usually 5000 to 1000000 eg 10000 to 1000000 such as 1000 to 50000 and preferably has a K value of 10 - 150 especially 15 - 50, wherein the K value is obtained from the
 15 relative viscosity in aqueous solution via the FIKENTSCHER'S Formula, from which the average molecular weight is calculated as described in USP 2,811,499. The Polymer has a hydrocarbon chain with pendant N-heterocyclic carbonyl groups, with the bonding to the chain via the heteroring -N- atom and the N- heterocyclic carbonyl groups as described further above. The aliphatic group or groups in the polymer may
 20 be part of the hydrocarbon chain, or bonded to it or to the N-heterocyclic carbonyl ring; the aliphatic group may be linear or branched and maybe alkyl eg of 1 - 40 eg 2 - 25 carbons or alkenyl eg of 2 - 20 carbons, especially methyl, ethyl, butyl or octyl, tetradecyl, hexadecyl, octadecyl, eicosyl, tricosyl or ethylene, butylene or octylene. The molar ratio of aliphatic group to heterocyclic carbonyl group in the Polymer is
 25 usually 1:99 to 20:80 eg 5 - 15 : 95-85.

The Polymer may be a copolymer having repeat units derived from at least one monomer which is an optionally alkyl substituted vinyl N-heterocyclic carbonyl compound) and at least one monomer which is an olefin; this copolymer may be simple copolymer formed by copolymerization of the monomers or a graft copolymer formed
 30 by grafting the olefin onto a polymer of the N-heterocyclic monomer. The Polymer may also be an alkylated derivative of a polymer of an optionally alkyl substituted (vinyl N-heterocyclic compound) especially a homopolymer of such a compound.

The optionally alkyl substituted vinyl N-heterocyclic carbonyl compound may be of general formula:



wherein each of R^{11} , R^{12} and R^{13} , which may be the same or different, represents a hydrogen atom or an alkyl group eg of 1 - 20 carbons, such as methyl, ethyl, butyl, hexyl, decyl or hexadecyl, and R^{10} represents an N-heterocyclic carbonyl group with the free valency on the N atom; preferably the N heterocyclic carbonyl group is as described above. The N-heterocyclic ring may contain 1-3 ring N atoms but especially 1 ring N atom and 0 - 2 other ring hetero atoms eg O or S, but especially no ring hetero atom; the ring may contain in total 1 or 2 rings, which may be saturated or ethylenically unsaturated such as a pyrrolidine, piperidine, quinoline or pyridine ring. Preferably R^{11} , R^{12} and R^{13} are hydrogen and R^{10} represents an N-(pyrrolidone), N-(2 pyrid-2-one) or N-(piperid-2-one) group.

The olefin is usually of 2 - 32 eg 4 - 18 carbon atoms and is generally a hydrocarbon. It is preferably an alkene, especially a linear alkene and has in particular a terminal olefin group. It is preferably a vinyl olefin eg of formula $CH_2 = CH - R^{14}$, where R^{14} is hydrogen or alkyl of 1 - 40 carbons, such as methyl, ethyl, propyl, butyl, hexyl or decyl, tetra decyl, octadecyl or octacosyl (so the olefin is tricosene). The olefin is preferably butylene octene-1 or dodecene-1, hexa decene-1, octadecene-1, eicosene-1 or tricosene-1.

The Polymer may be made by free radical copolymerizing the N-heterocyclic carbonyl compound eg N-vinyl pyrrolidone with the olefin eg butylene in solution in the presence of a peroxide catalyst. The Polymer may also be made by free radical grafting of the olefin onto a polymer of the N-heterocyclic carbonyl compound eg poly vinyl pyrrolidone (PVP) with K value as described above. The copolymerizations may incorporate structural units from the olefin into the hydrocarbon polymer chain and/or insert such units into the N-heterocyclic rings.

The Polymer may also be made by direct alkylation of the polymer of the N-heterocyclic carbonyl compound eg PVP with an alkylating agent eg an alkyl halide such as butyl bromide or octyl bromide, optionally in the presence of a base, such as triethyl amine.

Finally the Polymer may be a homo or copolymer of an alkyl substituted N-(alkenyl) heterocyclic compound in which the alkyl substituent may be in the N-heteroring and/or present in the alkenyl side chain; the alkyl substituent may be as is preferred for the aliphatic group on the Polymer described above. The Polymer may have structural units from an N-vinyl-alkyl ring substituted heterocyclic carbonyl compound, such as N-vinyl-3-methyl pyrrolid-2-one and/or from an N-butenyl-heterocycle carbonyl compound, such as N-butenyl-pyrrolid-2-one. Such Polymers

may be made by polymerization in solution in the presence of a free radical catalyst, in an analogous way to polyvinyl pyrrolidone.

Thus the preferred Polymers are aliphatic (N-heterocyclic carbonyl) polymers with units derived from N-vinyl pyrrolid-2-one and butylene (sold as Antaron P 904),
5 octylene, dodecylene, hexadecylene (sold as Antaron V216), eicosylene and tricosylene; the Antaron products are sold by International Speciality Products of Wayne, N.J., USA.

The Polymer may also be as Additive (xiii) a copolymer of (a) at least 1 ethylenically unsaturated N- heterocyclic ring compounds especially with at least one
10 of (b) a different ethylenically unsaturated N-heterocyclic ring compound, (c) an ethylenically unsaturated carbocyclic carbonyl compound, and (d) a polar ethylenically unsaturated compound, different from said N-heterocyclic compounds. Polymer Additive xiii preferably consists essentially of structural units derived from at least 2 of said (a)-(d) compounds, in particular (a), (b) and (d). Polymers (xiii) from heteroring
15 ring compounds with different size rings e.g. with differences of 1-3 in the numbers of ring atoms are preferred, especially ones with 5 and 7 membered heterorings. Examples of the ethylenically unsaturated N-heterocyclic ring compounds are ones described above in relation to Polymers (xi) especially N-vinyl-pyrrolidone and N-vinyl
20 omega caprolactam. The carbocyclic compound may be one with 4-8 eg. 6 or 7 ring atoms with the carbonyl group in the ring preferably adjacent to a carbon atom carrying the ethylenically unsaturated group which is preferably an alkenyl group of 2-6 carbon atoms especially with a terminal $\text{CH}_2=\text{CH}$ -group. The carbocyclic compounds are cyclic ketones with an unsaturated side chain. Examples of the carbocyclic compound are 2-vinyl- cyclohexanone and 2-vinyl-cycloheptanone. The
25 polar ethylenically unsaturated compound may be an ester of an alcohol containing more than 1 polar group and an unsaturated acid. The alcohol usually contains a hydroxyl group and at least one other hydroxyl group or aminogroup, which may be a primary secondary or especially tertiary amino group in particular in a non cyclic arrangement; thus the alcohol may be a diol or an amino alcohol, especially an aliphatic
30 one, such as a dialkylaminoalkanol, with 1-4 carbons in each alkyl and 2-4 carbons in the alkanol. 2-Dimethylamino ethanol is preferred. The unsaturated acid is usually an aliphatic alkenoic acid with 3-10 carbons such as acrylic or methacrylic or crotonic acid. This unsaturated ester is especially a (meth) acrylate ester of a dialkylamino alkanol in particular dimethylaminoethyl acrylate or methacrylate. Polymer Additive
35 xiii may be as described in WO94/12761, the disclosure of which is herein incorporated

by reference.

The Polymer may contain structural units in molar % derived from 10-90% of the N-heterocyclic compound, 10-90% of the carbocyclic compound and 10-90% of the polar ethylenically unsaturated compound. A preferred compound is a copolymer of N-vinyl pyrrolidone, N-vinyl-omega caprolactam and dimethylamino ethyl methacrylate, such as is sold as Antaron VC713 by International Speciality Products of Wayne, NJ.

The amount of said Polymer (xiii) is usually 10-1000% such as 50-300% or 90-250% based on the weight of the total of Additives (i) and (ii). Mixtures of the aliphatic (N-heterocyclic carbonyl) polymer (xii) and the copolymer (xiii) may be used especially in weight ratios of 10-90:90-10 in particular a majority of (xiii) eg. in weight ratio of (xii) to (xiii) of 10-40:90-60.

The Formulations preferably contain at least one anti-foaming agent (xiv) especially when the Additive (i) or (ii) has foaming activity, eg. when either contains at least one alkyl group of at least 8 carbon atoms. Examples of suitable anti-foaming agents are silicon containing compounds especially organosilicon oxygen or nitrogen compounds, such as polysiloxanes, including cyclic polysiloxanes, silicon polyethers, polysilazanes and fluorosiloxanes. Alkylpolysiloxanes are preferred especially dimethyl polysiloxanes such as 3556 from Th. Goldschmidt KG and AF 1520 from Dow Corning. The silicon anti-foaming agents are usually used as water dispersible emulsions. Silicon free anti-foaming agents, such as suds depressants used in detergents, may also be used. The amount of the anti-foaming agent is usually 10-70ppm e.g. about 40ppm (based on the total water present), or 10-70ppm e.g. about 40ppm (based on the total weight of Additives (i) and (ii)).

Formulations comprising Additive (i) and (ii) and preferably at least one of Additive (ix) - (xiii) may be used in total amount of 50-10,000 ppm, especially 150-2000 ppm, or 2000-8000 such as 4000-6000 ppm relative to the total water in the medium in which hydrates may form (including any water added in the formulation).

The Formulation may also contain another hydrate inhibitor and/or a water dispersant or surfactant, in particular an anionic one such as sodium dodecyl sulphonate or stearic acid and in amount of 1-10% of the Formulation weight and/or a biocide, e.g. formaldehyde, e.g. in amount of 10-10,000 ppm and/or a metal complexant such as citric acid (e.g. in amount of 10-10,000 ppm) all amounts being in relation to the total weight of the Formulation.

The Formulations may be used to retard or inhibit hydrate formation in the

same manner as the individual Additives, as described above.

The inhibitor Additives and Formulations of the present invention are suitable for use in media containing water and gas, in particular in the petroleum, natural gas and gas industries. The gas may be a hydrocarbon normally gaseous at 25°C and 100 KPa pressure, such as an alkane of 1-4 carbon atoms eg methane, ethane, propane n or isobutane, or an alkane of 2-4 carbon atoms eg ethylene, propylene, n- or isobutene; the gas preferably comprises by weight at least 80% and especially at least 90% of methane with 0.1 - 10% eg 1-5% C₂ hydrocarbon and 0.01 - 10% eg 0.05 - 5% C₃ hydrocarbon. A natural gas, which may or may not have been purified or processed is preferred. The gas may also contain nitrogen eg in amount of 0.01-3% by weight and/or carbon dioxide eg in amount of 0.1 - 5% such as 0.5 - 2% by weight. The Additive (i) and (ii) can be more effective than poly vinyl pyrrolidone in the inhibition of gas hydrate formation, especially when the gas comprises carbon dioxide.

In particular, they may be suitable for use during the transportation of fluids comprising gas and water eg from oil or gas wells. They may also be suitable for use in oil based drilling muds to inhibit hydrate formation during drilling operations.

In another aspect therefore the invention provides an oil based drilling mud, which comprises as hydrate inhibitor at least one Additive, as such or in a Formulation.

When used during the transportation of fluids, e.g. gases with water and optionally oil eg. condensate in conduits such as pipelines the inhibitors may be injected continuously or batchwise into the conduit upstream of conditions wherein hydrate formation may occur. Conditions under which gas hydrates may form are usually at greater than -5°C eg greater than 0°C such as 0 to 15°C eg 1 - 10°C and pressures eg of 0.1 - 30 MPa eg 1 - 15 MPa the temperature of onset of gas hydrate formation depending on the pressure, and the presence of, and concentration of, salt in the water. As the temperature decreases and the pressure increases and the concentration of salt decreases the greater is the likelihood for hydrate formation to happen in the absence of the Additives and Formulations of the invention. Thus the conditions of use of the Additive are ones such that in its absence a gas hydrate may form. In the absence of the Additive ice may also form in addition to the gas hydrate especially at temperatures of -5°C to 5°C. The pH of the water eg in the pipeline after addition of the Additives or Formulation is usually 3-9, especially 3.3-5 or 5-7.5.

In drilling operations the inhibitors may be added to the drilling muds in the mud tank at the wellhead.

The invention is illustrated in the following Examples.

Examples

To assess the efficiency of hydrate inhibitors suitable for use in the method of the present invention, tests were carried out using the following procedure:

The hydrate inhibitor test apparatus consisted of a simple 316 stainless steel
5 pressure cell, with a usable internal volume of 1000
cm³ with a thermostated cooling jacket, a sapphire window, an inlet
and outlet and a platinum resistance thermometer. The cell contained water which
was stirred by a magnetic pellet. Temperature and pressure were monitored and the
results provided on a computer data logger, gas hydrates were also detected visibly
10 using a time lapse video recording system. Before each test the cell was cleaned
thoroughly by soaking successively in 10% aqueous hydrochloric acid for 1 hour, 10%
aqueous sodium hydroxide solution for 1 hour and then double distilled water.

Into the cell was placed 200 cm³ of pre-chilled double distilled water with or
without the chemical to be tested. A PTFE stirrer pellet was then placed in the cell and
15 the pH of the solution measured with subsequent adjustment if desired by the addition
of small but concentrated amounts of hydrochloric acid or sodium hydroxide. After
sealing the cell the water was then stirred at 500 rpm and allowed to cool to the
operational temperature of 4°C. When this temperature was reached the stirrer was
stopped and the video recorder started. Methane was then admitted to the cell until
20 the pressure reached 70 bar (7 MPa) and the temperature, pressure and time were
noted. The stirrer was restarted to run at 500 rpm and the time noted. Hydrates were
observed to form in the vessel when the solution in the vessel turned opaque,
coincident with which was a sharp temperature increase of about 0.2°C and a gradual
pressure reduction. The time from first contact of water and gas to formation of
25 hydrate was read from the logger.

The experimental conditions are a very severe and accelerated test of gas
hydrate formation and inhibition. The amounts of the Additive are expressed in ppm
based on the volume of water. The inhibition time results given are an average of
several results.

30 In the Examples, the following Additives were used :

Additive (i)(a) Benzalkonium chloride, which was benzyl
hexyldimethylammonium chloride

Additive (i)(b) was a corrosion inhibitor blend sold by Nalco as "NAL 1272"
believed to contain a tertiary amine and/or quaternary ammonium salt and/or aliphatic
35 imidazoline, and possibly also a phosphate ester.

Additive (i)(c) was a corrosion inhibitor which was N-2- aminoethyl -2-oleylimidazoline, sold by BP Chemicals as IC 100.

Additive (i)(d) was a corrosion inhibitor, which was an alkyl benzyl dimethylammonium chloride sold by Hoechst under the Trade Mark DODIGEN 5462.

5 Additive (i)(e) was a corrosion inhibitor (sold under the Trade Mark "Champion" RU189 by Champion Technologies Inc., Texas, USA), which is believed to be a 1:1 mixture of quaternary ammonium salt and an aliphatic imidazoline.

Additive (ii)(a) was tetra-n-butylammonium bromide.

Additive (ii)(b) was tetra-n-pentylammonium bromide.

10 Additive (xii) was a "butylated polyvinyl pyrrolidone" sold under the Trade Mark "Antaron" P 904 by International Speciality Products of Wayne, N.J., USA, which is a water soluble copolymer powder with structural units derived from 90% N-vinyl pyrrolidone and 10% butylene and prepared by polymerization with t-butylperoxide; it is believed to be a graft copolymer of poly vinyl pyrrolidone (K30)
15 and butylene, with the butylene structural units in the pyrrolidone ring and/or part of the hydrocarbon backbone and/or pendant thereon. The chemical has a weight average molecular weight of about 16000.

Additive (xiii) was a vinyl pyrrolidone copolymer sold under the Trade Mark "Antaron" VC 713 by International Speciality Products of Wayne, NJ, USA, which is a
20 powder of a copolymer which is terpolymer with structural units from N-vinyl pyrrolidone, N-vinyl-omega caprolactam and-dimethylaminoethyl methacrylate.

Additive (xiv) was an anti-foaming agent, which was a polydimethylsiloxane sold by Dow Corning under the Trade Mark AF1520.

Examples 1 - 5

25 The formulations were made up and added to the water so it contained the Additives below in amounts (in ppm relating to total water present). The results (averaged over several repeat experiments) were as follows:

30

35

Additive, Amount (ppm)								
EXP.	(i)	(ii)	(xii)	(xiii)	(xiv)	Total	pH	Inhibition Time/Mins
0	-	-	-	-	-	-	-	6
1	(c)500	(b)1000		1000		2500		569
2	(d)500	(b)1000		1000		2500	6.2	2039
3	(a)1000	(b)2000		2000		5000		294
4	(e)1000	(b)2000		2000		5000		1201 ^x
5	(e)1000	(b)1500		2000		3100	8.3	1360

^xdenotes single result.

Examples 6 - 14

- 5 In these Examples, the process of Examples 1 - 5 were repeated with the methane replaced by a synthetic gas mixture (simulating natural gas) comprising by weight 95.3% methane, 3% ethane, 0.5% propane, 1% carbon dioxide and 0.1% each of iso-butane and n-butane. The pH of the medium was 4.0. The test was performed as described in Examples 1 - 5 apart from use of 5°C as the operational temperature.

The results (averaged over several repeat experiments) were as follows:

10

Additive, Amount (ppm)								
EX.	(i)	(ii)	(xii)	(xiii)	(xiv)	Total	pH	Inhibition Time/Mins
6	(b)400	(a)1500	500	1500	40	3940		504
7	(a)400	(a)1500		1500	40	3440	6.6	285
8	(a)400	(a)1500	500	1500	40	3940		456
9	(d)400	(b)1500	500	1500	40	3940		1543 ^x
10	(a)1000	(b)2000		2000		5000		323
11	(b)400	(b)1000		1000		2400	6	159
12	(b)400	(b)1500	500	1500	40	3940		4500 ^x
13	(b)*400	(b)1500	500	1500	40	3940		1186
14	(e)500	(b)2000		2000		4500		1290

^xDenotes a single result

*Denotes addition of (b) in mono butyl ethylene glycol ether (10% based on total water present)

Example 15

An inhibition blend was prepared with the proportions as in Example 6 but with a total of 4995ppm (i.e. 510ppm of (i)(b), 1900ppm (ii), 635ppm (xii), 1900ppm (xiii) and 50ppm (xiv) as well as the monobutyl glycol ether.

5 This inhibitor blend was tested in a field trial in the North Sea. Wet gas from a well was received at a first platform and was then passed subsea where it met gas from a second platform and the combined gas passed in a subsea line to a third platform. The wet gas arriving at the third platform comprised natural gas, which was in a mole% carbon dioxide 1.1%, nitrogen 1.6%, methane 92.95%, ethane 3.22%, propane 10 0.57% and C₄+ hydrocarbons 0.47%, as well as water which was in amount of about 1.4 barrels per day per million standard cu.ft. of gas (bbld/mmmscf) and condensate in amount of about 0.1 bbld/mmmscf. The gas at the first platform was at 30°C and 7.5MPa (75bar) but cooled subsea. The gas on the second platform was under comparable conditions but was passed through a valve on the second platform, which 15 could be partly closed to a fixed position, resulting in extra cooling to 8-9°C at the valve, which gave temperatures of about 10°C in the eventual subsea line just before the third platform and resulted in solid gas hydrates in the absence of added inhibitors. Formation of hydrates was shown by an increase in the back pressure in the line upstream of the valve, or by a reduction in the amount of water exiting the gas line at 20 the third platform.

Methanol had been used as inhibitor in a blank trial, methanol addition was stopped and no other inhibitor added; 30hrs later the amount of exit water at the third platform had reduced to zero and after 46hrs the back pressure started to increase denoting significant solid gas hydrate formation. Methanol was then added and the 25 valve reopened to raise the temperature and to remove the hydrates from the line.

Then into the gas on the first and second platforms with the valve open was added continuously the inhibitor blend for 4hrs until the concentration of ingredients in the exit gas line to the third platform had become steady. The valve was partly closed to the fixed position; the blend was added continuously into each gas at 4995ppm total 30 level (relative to the water content of each gas) for 100hr while monitoring the exit water flow rate, which went from an initial 0.7bbls/mmmscf quickly to 1.4 bbls/mmmscf, where it remained steady denoting absence of formation of hydrates. The back pressure did not change over this period. The inhibitor blend addition rate was then reduced to a total of 3300ppm and over the next 30hrs again the water flow rate in 35 bbl/mmmscf and the pressure remained substantially constant denoting absence of

hydrates. The flow of inhibitor blend was then stopped resulting in a slow reduction in the water flow to zero and a subsequent increase in the back pressure, denoting reformation of hydrates. The valve was then opened and methanol was then added to clean the line of hydrates.

5 Example 16-18 and Comp. A and B

In these Examples the process of Example 6 was used with a temperature of 4.5°C, a gas pressure of 37 bar the Additive mixture that of Example 6 (but used at varying levels), use of 200ml double distilled water in the cell or 100ml double distilled water and 100ml hexane, and a gas, whose molar composition was 87.57% methane, 7.8% ethane, 2.69% propane, 0.26% isobutane, 0.44% n butane, 0.15% pentanes, and 1.09% carbon dioxide.

The results were as follows (averaged over several experiments):

Additive (ppm on total water)								
EX.	(i)	(ii)	(xii)	(xiii)	(xiv)	Total	Hexane	Inhibition Time
16	(b)400 ^x	(a)1500	500	1500	40	3940	Yes	48hr +
17	(b)200 ^x	(a)750	250	750	20	1970	Yes	48hr +
A	-	-	-	-	-	-	Yes	3.5mins
18	(b)400 ^x	(a)750	250	750	20	2170	No	58hr ^{xx}
B	-	-	-	-	-	-	No	11mins

x Denotes addition of (b) in monobutyl ethylene glycol ether (10% on total water)

xx Denotes a small amount of hydrate present in vessel

15 Example 19-21 and Comp. C and D

The process of Example 16 was repeated with a gas pressure of 28 bar and a gas of molar composition 88.12% methane, 8.04% ethane, 2.18% propane, 0.23% isobutane, 0.37% n butane, 0.13% pentanes and 0.93% carbon dioxide, Additives of Example 6 or Example 12, (but at different levels) and instead of the hexane, 100ml of a crude reservoir oil from the North Sea. The results were as follows, averaged over several experiments.

Additive (ppm on total water)								
EX.	(i)	(ii)	(xii)	(xiii)	(xiv)	Total	Oil	Inhibition Time
19	(b)400 ^x	(a)1500	500	1500	40	3940	Yes	48hr +
20	(a)400 ^x	(a)1500	500	1500	40	3940	Yes	48hr + ^{xx}
C	-	-	-	-	-	-	Yes	6 min
21	(b)400 ^x	(a)750	250	750	20	2170	No	68hr +
D	-	-	-	-	-	-	No	14min

x Denotes addition of (b) in monobutyl ethylene glycol ether (10% on total water)

xx Denotes the presence of hydrate lumps in the gas space over the liquid, but none in the liquid.

5 Example 22-5 and Comp. Examples E and F

The process of Example 16 was repeated with operating temperatures of 4°C or 8°C and gas pressures of 70 bar and a gas molar composition as in Example 6-14. The results were as follows (averaged over several experiments).

Additive (ppm on total water)								
EX.	(i)	(ii)	(xii)	(xiii)	(xiv)	Total	Oil	Inhibition Time
22	(b)400 ^x	(a)1500	500	1500	40	3940	Yes	480mins (4°C)
E	-	-	-	-	-	-	No	5.2min (4°C)
23	(b)400 ^x	(a)750	250	750	20	2170	No	192hr + (8°C)
24	(b)400 ^x	(a)400	100	400	40	1340	No	71hr (8°C)
25	(b)200 ^x	(a)750	250	750	20	1970	Yes	168hr+ (8°C)
F	-	-	-	-	-	-	No	153min (8°C)

10 x Denotes addition of (b) in monobutyl ethylene glycol ether (10% on total water)

Examples 26-8 and Comp. G

The process of Example 16 was repeated with a temperature of 5.0°C, a gas pressure of 70 bar and a molar composition of gas of 84.36% methane, 6.79% ethane, 2.54% propane, 0.43% isobutane, 0.77% n butane, 0.49% pentanes, 3.36% carbon dioxide and 0.81% nitrogen and in the cell 100ml double distilled water and 100ml crude reservoir oil from a North Sea field different from that in Examples 19-21. The results were as follows (averaged over several experiments).

15

Additive (ppm on total water)							
EX.	(i)	(ii)	(xii)	(xiii)	(xiv)	Total	Inhibition Time
26	(a)1000	(b)2500	-	2500	-	6000	14hr 43 mins
27	(b)400 ^x	(b)1500	500	1500	40	3940	13hr 26 mins
28	(a)1000	(b)1500	500	1500	-	4500	8hr 18 mins
G	-	-	-	-	-	-	0.5min

x Denotes addition of (b) in monobutyl ethylene glycol ether (10% on total water)

5

10

15

20

25

Claims

1. A method of inhibiting or retarding hydrate formation, which method comprises adding additives (hereinafter called Additives) which comprise (i) a corrosion inhibitor and (ii) a salt which is of formula $[R^1(R^2)XR^3]^+Y^-$, wherein each of R^1 , R^2 and R^3 is bonded directly to X, each of R^1 and R^2 , which may be the same or different is an alkyl group of at least 4 carbons, X is S, NR^4 or PR^4 , wherein each of R^3 and R^4 which may be the same or different represents hydrogen or an organic group, with the proviso that at least one of R^3 and R^4 is an organic group of at least 4 carbons, and Y is an anion, the additives being added in an amount effective to inhibit or retard hydrate formation, to a medium susceptible to hydrate formation.
2. A method according to claim 1 characterized in that the weight proportion of Additive (i) to Additive (ii) is 10-45 : 90-55.
3. A method according to claim 1 or 2 characterized in that in Additive (ii) each of R^1 and R^2 is an alkyl group of the 4-6 carbons, X is NR^4 or PR^4 , R^3 is an alkyl group of 1-24 carbons and R^4 is an alkyl group of at least 4 carbons.
4. A method according to claim 3 characterized in that Additive (ii) is a tetra n butyl or tetra n-pentyl ammonium halide.
5. A method according to any one of the preceding claims characterized in that Additive (i) comprises a benzyl alkyl dimethyl ammonium chloride.
6. A method according to any one of the preceding claims, characterized in that Additive (i) comprises a tertiary amine or imidazoline.
7. A method according to any one of the preceding claims characterized in that it comprises also adding at least one of (a) an Additive (ix), which is at least one water soluble polymer of a polar ethylenically unsaturated compound, and (b) an Additive (x) which is a hydrophilic colloid.
8. A method according to any one of the preceding claims characterized in that it

comprises also adding an Additive (xii) which an aliphatic (N heterocyclic carbonyl) polymer with a hydrocarbon backbone.

9. A method according to claim 8 characterized in that said Additive (xii) is a polymer with units from N-vinyl pyrrolidone and an alkene of 4-18 carbon atoms.

5 10. A method according to any one of the preceding claims characterized in that it comprises also adding an Additive (xiii) which is a copolymer of (a) at least 1 ethylenically unsaturated N- heterocyclic ring compound with at least one of (b) a different ethylenically unsaturated N-heterocyclic ring compound, and (c) a polar ethylenically unsaturated compound, different from said N-heterocyclic compounds.

10 11. A method according to claim 10 characterized in that said Additive (xiii) is a copolymer of N-vinylpyrrolidone, N-vinylomegacapolactam and dimethyl amino ethyl methacrylate.

12. A method according to claim 11 characterised in that it comprises adding to said medium 200-1500 parts of Additive (i), 500-5000 parts of Additive (ii), with
15 Additive (xii) and Additive (xiii) and a total of 2000-8000 parts of Additives, based on the total water volume of the medium, and a weight ratio of Additive (xii) to (xiii) of 10-40 : 90-60 and a percentage of Additive (xiii) to the total of Additives (i) and (ii) of 50-300%.

13. A Formulation for use as a gas hydrate inhibitor which comprises a blend of
20 Additives (i) and (ii) and optionally at least one of (ix), (x), (xii) and (xiii) said Additives being defined in any one of the preceding claims.

14. Method of transporting through a pipeline a fluid comprising water and a gas susceptible to form hydrates, which comprises treating said fluid with Additive (i) and Additive (ii) and optionally at least one of Additives (ix), (x), (xii) and (xiii) as defined
25 any one of claims 1-12 or with a formulation as defined in claim 13, upstream of a locus in said pipeline wherein gas hydrates may be formed in the absence of said Additives.

15. Use of Additives (i) and (ii) and optionally at least one of Additives (ix), (x), (xii) and (xiii) as defined in any one of claims 1-12 or a formulation as defined in claim
30 13 for the inhibition or retardation of the formation of gas hydrates.

16. An oil based drilling mud, which comprises a hydrate inhibitor which is Additives (i) and (ii) and optionally at least one of Additives (ix), (x), (xii) and (xiii) as defined in any one of claims 1-12 or a formulation as defined in claim 13.

INTERNATIONAL SEARCH REPORT

Inter Application No
PCT/GB 95/01801

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 E21B37/06 C10L3/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 6 E21B C10L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
P, Y A	WO, A, 95 17579 (SHELL INT RESEARCH ; SHELL CANADA LTD (CA)) 29 June 1995 see claims 1-9, 14 ---	1 1, 3, 4
P, Y	WO, A, 94 24413 (BP CHEMICALS) 27 October 1994 see claim 1 -----	1

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- "&" document member of the same patent family

Date of the actual completion of the international search

16 November 1995

Date of mailing of the international search report

24 -11- 1995

Name and mailing address of the ISA
European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+ 31-70) 340-3016

Authorized officer

De Herdt, O

INTERNATIONAL SEARCH REPORT

Information on patent family members

Patent Application No

PCT/GB 95/01801

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO-A-9517579	29-06-95	US-A- 5460728 AU-B- 1316895	24-10-95 10-07-95
WO-A-9424413	27-10-94	NONE	

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☒ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☒ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.